



Specification (Test Condition, 25 °C)

1. Housing Material/ Color..... ABS/Black
2. Voice Coil Impedance 8 Ohm (at 1 KHz)
3. Voice Coil Dimension Ø 25.4 mm(Dia.)
4. Magnet Size Ø70*32*10 mm(Dia.* dia.*H)
5. Power Rating RMS 15 W
6. Power Rating Peak 20W
7. S.P.L. Min.105 dB(at 1 meter/1W)
8. Resonant Frequency 2KHz±10%
9. Rated Frequency Range 500~ 8500Hz
10. Load Test 8 Hours (at 15w)
11. Heat Test 8 Hours (at 60°C)
12. Operating Temperature range -20 ~ +60°C
13. Store Temperature..... - 20 ~ +70°C
14. Wires Connection Ø0.2×16 2-black(Non-polarized)
15. Weight 430 ±10g

				KEPO NINGBO KEPO ELECTRONIC CO.,LTD http://www.chinaacoustic.com	
				Electronic horn	
No.	DESCRIPTION	APPROVED	DATE	SH-8088	
TOLERANCES UNLESS NOTED OTHERWISE X .X ± .XXX ± 90° FORMED ±2° ANGLES -1°		APPROVALS		DATE	UNIT
FIRST ANGLE PROJECTION		DRAWN		CHECKED	mm
APPROVED		05.09.12		SCALE	DWG NO. KP4.840.447
				NOT TO SCALE	SHEET
				VER 1.0	