



## SPECIFICATION

- 1. Rated Voltage ..... 1.5 V
- 2. Operating Voltage ..... 1~2 V
- 3. Max. Rated Current ..... 10mA
- 4. Coil Resistance .....  $50 \pm 7.5 \Omega$
- 5. Coil Impedance ..... 140  $\Omega$
- 6. Min. Sound Pressure Level ..... 80dB/10cm
- 7. Resonant Frequency ..... 2048Hz
- 8. Case Material ..... NORYL
- 9. Operating Temperature ..... -20~+70°C
- 10. Store Temperature ..... -30~+80°C
- 11. Weight ..... 2g

				<b>KEPO</b> NINGBO KEPO ELECTRONIC CO.,LTD <a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a>	
				<b>Magnetic Buzzer</b> <b>KP12-185CL</b>	
No.	DESCRIPTION	APPROVED	DATE		
TOLERANCES UNLESS NOTED OTHERWISE: .X * .XX * .XXX * 90° FORMED +2° ANGLES ±° FIRST ANGLE PROJECTION		APPROVALS			
		DRAWN	DATE		
		CHECKED		UNIT	DWG NO.
		APPROVED	05.08.01	mm	KP3.840.663.01
			SCALE	NOT TO SCALE	SHEET
			VER	1.0	