



# SPECIFICATION

- 1. Rated Voltage ..... 5VDC
- 2. Operating Voltage ..... 4~7VDC
- 3. Max. Rated Current ..... 40mA
- 4. Coil Resistance .....  $40 \pm 5 \Omega$
- 5. Coil Impedance .....  $80 \Omega$
- 6. Min. Sound Pressure Level ..... 87dB/5VDC/10cm
- 7. Resonant Frequency ..... 3200Hz
- 8. Case Material ..... PBT
- 9. Operating Temperature .....  $-20 \sim +70^\circ\text{C}$
- 10. Store Temperature .....  $-30 \sim +80^\circ\text{C}$
- 11. Weight ..... 1g

|  |             |           |          |   |         |
|--|-------------|-----------|----------|---|---------|
|  |             |           |          | <b>KEPO</b> NINGBO KEPO ELECTRONIC CO.,LTD<br><a href="http://www.chinaacoustic.com">http://www.chinaacoustic.com</a> |         |
|  |             |           |          | <b>Magnetic Buzzer QUARTZ</b>   |         |
|  |             |           |          | <b>DRP9650-5-3.2</b>  |         |
| No.  | DESCRIPTION | APPROVED  | DATE     |   |         |
| <small>           TOLERANCES UNLESS NOTED OTHERWISE:<br/>           .X *<br/>           .XX *<br/>           .XXX *<br/>           90° FORMED ±2°<br/>           ANGLES ±1°<br/>           FIRST ANGLE PROJECTION         </small> |             | APPROVALS |          | DATE  |         |
|  |             | DRAWN     |          |   |         |
|  |             | CHECKED   |          | UNIT  | DWG NO. |
|  |             | APPROVED  | 06.07.20 | mm  | OEM2259 |
|  |             |           |          | SCALE   | SHEET   |
|  |             |           |          | NOT TO SCALE  | VER 1.0 |