



QUARTZ CRYSTALS

MHz range

SMD-version

model	KX - 13		
frequency range	6,0 ~ 160,0 MHz		
mode	fundamental, 3 rd overtone, 5 th overtone		
operating temperature	standard -20° ~ + 70° C available -40° ~ + 85° C (= KX-13T) available -40° ~ + 105° C (= KX-13E)		
frequency tolerance at +25° C	standard ± 30 ppm available ± 10 ~ ± 50 ppm		
temperature tolerance at -20° ~ + 70° C -40° ~ + 85° C -40° ~ + 105° C	standard ± 50 ppm, available ± 10 ~ ± 30 ppm, standard ± 100 ppm, available ± 20 ~ ± 50 ppm standard ± 120 ppm, available ± 30 ~ ± 80 ppm		
load capacitance C _L	standard 16 pF available 12 ~ 20 pF		
series resonance R ₁ max.	fundamental	6,0 ~ 7,00 MHz	120 Ohm
		7,1 ~ 10,99 MHz	100 Ohm
		11,0 ~ 13,99 MHz	50 Ohm
		14,0 ~ 15,99 MHz	40 Ohm
	3 rd overtone	16,0 ~ 40,50 MHz	30 Ohm
		35,0 ~ 39,99 MHz	100 Ohm
		40,0 ~ 49,99 MHz	80 Ohm
	5 th overtone	50,0 ~ 90,00 MHz	50 Ohm
		90,0 ~ 260,00 MHz	100 Ohm
aging (first year)	standard: ± 5 ppm, possible ± 1 ppm		
shunt capacitance C ₀ max.	7,0 pF		
drive level in mW	0,05		
RoHS	since production start		
contents of reel	1000 pcs.		
part no.	12.87900-12.87999		

