



+极标志Polarity+

编织线braided wire

SPECIFICATION

Sound

- 1. Resonant Frequency 2.6 ± 0.3 kHz
- 2. Static Capacitance $150000 \pm 30\%$ (pF) at 100 Hz
- 3. Resonant Impedance 150 Max (Ω)
- 4. Input Voltage 30 Vp-p Max
- 5. Operating Temperature -20 - $+70$ ($^{\circ}\text{C}$)
- 6. Storage Temperature -20 - $+80$ ($^{\circ}\text{C}$)
- 7. Metal Material SUS304



Glue-Protection Coating

技术要求:

- 1, 带标记点一面为正极面, 标记点直径1.0mm
- 2, 银层上焊点直径控制在 2.3 ± 0.5 mm,
- 3, 2-GJ 1x4铜绞线; L=80±5 mm,

				NINGBO VOISE ELECTRONICS CO.,LTD http://www.nbvoise.com	
No.	DESCRIPTION	APPROVED	DATE	Piezoelectric Element VS-27G-26ASLG80G	
TOLERANCES UNLESS NOTED OTHERWISE: .X ± .XX ± .XXX ± 90° FORMED +2° ANGLES -1°		APPROVALS	DATE		
FIRST ANGLE PROJECTION		CHECKED		UNIT mm	DWG NO. VS20200709015
		APPROVED	20.07.09	SCALE	SHEET
				VER	1.0