

SPECIFICATION

FOR APPROVAL

Customer : _____

Product Name : Piezo Buzzer

Model Name : VSI2616F28L100WP

Drawing No. : VS20241018010

Signature of Voise

Approved by	Checkde by	Issued by	Date

 福爱斯电子有限公司
VOISE ELECTRONICS CO.,LTD.

Address:No 96 Mogao Dongqian Lake Industrial Area ningbo,China,
Tel:0086-0574-87773030;Fax:0086-0574-87471600 P.C.315121
<http://www.nbvoise.com> Email:sales@nbvoise.com

Specification for Piezoelectric Transducer		Page	2/3
		Revision No.	1.0
Model No.:	VSI2616F28L100WP	Drawing No.	VS20241018010

1. General Characteristics

- 2.1 Out-Diameter : 26 mm
- 2.2 Height : 16 mm
- 2.3 Weight : 9 g
- 2.4 Operating Temperature : -20~+60°C without loss of function
- 2.5 Store Temperature : -30~+70°C without loss of function

2. Electrical and Acoustic Characteristics.

Test condition :15 ~ 35 °C Temp., 25% ~ 75% RH,86~106 kPa Refer to IEC60268-1

No	Items	Specification
1	Rated Operating Voltage	12VDC
2	Operating Voltage range	3-18VDC
3	Max Rated Current	35 mA at 12VDC
4	Min Sound Pressure Level	90 dB at 12VDC 2.8kHz/30cm;80dB/3VDC/30cm
5	Resonance Frequency(fo)	2.8 kHz ± 500Hz
6	Tone Nature	Continuous
7	Shell Material	ABS (Black)
8	Waterproof IP	IP67

Specification for Piezoelectric Transducer		Page	3/3
		Revision No.	1.0
Model No.:	VSI2616F28L100WP	Drawing No.	VS20241018010

3. Dimensions

